

_include_wsc_proofreader_cloud_initialization_autosearch

Define the required configuration options in WEBSPELLCHECKER_CONFIG.

- The configuration options can be added as a script directly on the page or loaded from *.js file (e.g. wscbundle_config.js) where you define these options.
- It can be added to any location on a web page before or after the wscbundle.js script. However, if you add wscbundle.js **asynchronously**, the configuration options must be loaded **before** the script.

Required options for the WProofreader Cloud:

- Specify your **serviceld**. It is a required option for the service activation.
- Enable autoSearch functionality using the **autoSearch** parameter.

This is an example of the defining WEBSPELLCHECKER_CONFIG in a separate script directly on a web page.

```
<script>
    window.WEBSPELLCHECKER_CONFIG = {
        autoSearch: true,
        lang: 'auto', // set the default language
        serviceId: 'your-service-ID' // the activation key for the Cloud-based version
    };
</script>
```



Alternatively, you can create a *.js file (e.g. wscbundle_config.js) with WEBSPELLCHECKER_CONFIG on your end and then load it from the file on your web page as shown in example below.

This is an example of the **wscbundle_config.js** file with WEBSPELLCHECKER_CONFIG.

wscbundle_config.js

```
window.WEBSPELLCHECKER_CONFIG = {
    autoSearch: true,
    lang: 'en_US',
    serviceId: 'your-service-ID'
};
```

Here is an example of the script that you need to add on your web page with the path to **wscbundle_config.js**.

```
<script type="text/javascript" src="[path_to_config]/wscbundle_config.js"></script>
```