

`_include_wsc_dialog_options_html_editable_controls`

WSC Dialog Options for HTML Editable Controls

wsc_schemaidentifier MANDATORY

Description:	wsc_schemaidentifier option sets a schema identifier (look&feel) of WSC Dialog.
Parameter type:	Number
Default value:	18
Possible values:	<ul style="list-style-type: none">• 18 – open as a separate pop-up window.• 118 – open as a modal window.

Example:

```
schemaIdentifier: 118,
```

[Back to the top...](#)

ctrl MANDATORY

Description:	ctrl option defines an element identifier.
Parameter type:	String
Default value:	None
Possible values:	Any existing element ID.

Example:

```
ctrl: 'your_element_ID',
```

[Back to the top...](#)

lang MANDATORY

Description:	lang option sets a language short code of the default language that will be used for spell checking.
Parameter type:	String
Default value:	en_US (American English)
Possible values:	<ul style="list-style-type: none">• Default languages short codes• Additional languages short codes

Example:

```
lang: 'en_GB',
```

[Back to the top...](#)

title

Description:	title option sets a title name of WSC Dialog.
--------------	--

Parameter type:	String
Default value:	WebSpellChecker
Possible values:	Any name of a title.

Example:

```
title: 'WebSpellChecker Dialog',
```

[Back to the top...](#)

customDictionaryIds

Description:	customDictionaryIds option specifies an identifier of custom dictionary.
Parameter type:	String
Default value:	None
Possible values:	IDs of custom dictionaries separated with commas (',').

Example:

```
customDictionaryName: '1,3001';
```

[Back to the top...](#)

userDictionaryName

Description:	userDictionaryName option predefines a specific user dictionary that will be used with WSC Dialog.
Parameter type:	Array
Default value:	None
Possible values:	Any name of a user dictionary.

Example:

```
userDictionaryName: 'user_dictionary_name';
```

[Back to the top...](#)

cmd

Description:	cmd option sets an active tab which should be shown on the dialog opening.
Parameter type:	String
Default value:	spell
Possible values:	<ul style="list-style-type: none"> • spell – spell checking tab; • thes – thesaurus tab; • grammar – grammar checking tab.

Example:

```
cmd: 'thes';
```

[Back to the top...](#)

height

Description:	height option sets the height in pixels of WSC Dialog.
Parameter type:	Number
Default value:	534
Possible values:	Any height size in pixels.

Example:

```
height: 534;
```

[Back to the top...](#)

width


Description:	width option sets a dialog width in pixels.
Parameter type:	Number
Default value:	514
Possible values:	Any width size in pixels.

Example:

```
width: 514;
```

[Back to the top...](#)

top


Description:	top option sets a top margin value in pixels (initial –Y coordinate). <div> top option is applicable and can be used only if schemaldentifier is set to 18.</div>
Parameter type:	Number
Default value:	0
Possible values:	Any top margin value in pixels.

Example:

```
top: 0;
```

[Back to the top...](#)

left

Description:	left option sets a left margin value in pixels (initial –X coordinate). <div> left option is applicable and can be used only if schemaldentifier is set to 18.</div>
Parameter type:	Number

Default value:	0
Possible values:	Any left margin value in pixels.

Example:

```
left: 0;
```

[Back to the top...](#)

autoClose

Description:	autoClose option defines if the WSC Dialog window should be auto-closed.
Parameter type:	String
Default value:	None
Possible values:	<ul style="list-style-type: none">• no – no auto-closing.• yes – WSC Dialog will be closed after all misspellings are replaced with suggested corrections or ignored.• nomisspellings – WSC Dialog will be closed if no misspellings detected in the given text.

Example:

```
autoClose: 'yes',
```

[Back to the top...](#)
