

# \_include\_configuring\_server\_scayt\_plugin\_for\_froala\_editor

This guide outlines the main steps that you need to follow in order to integrate and configure the SCAYT plugin with [Froala Editor](#). Steps described below are applicable to the Server version of SCAYT.

## 1. Initializing Froala Editor

Before integrating and configuring the SCAYT plugin, Froala Editor should be properly configured in your web application. If you haven't done it yet, refer to the [Froala Editor's Get Started](#) instructions on the Froala Editor official website.

## 2. Adding SCAYT Script and Styles

As soon as Froala Editor is properly set on you page, add a script for the SCAYT plugin and define its styles as follows:

- Go to an official [Froala Editor's CDN](#).
- Find and copy a link to **spell\_checker.min.js** for your version of Froala Editor.
- Find and copy a link to **spell\_checker.min.css** styles file.
- Add a script to SCAYT plugin to define styles file as in the sample below:

```
<script src='https://cdnjs.cloudflare.com/ajax/libs/froala-editor/x.x.x/js/third_party/spell_checker.min.js'></script>
<link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/froala-editor/x.x.x/css/third_party/spell_checker.min.css" type="text/css" />
```

## 3. Creating Froala Editor Instance with Default SCAYT Options

Create a Froala Editor instance and define required SCAYT parameters and options as in the sample below.

```
$('#editor1').froalaEditor({
  scaytAutoload: true,
  pluginsEnabled: ['spellChecker'],
  toolbarButtons: ['bold', 'italic', 'spellChecker', '|', 'undo', 'redo'],
  toolbarButtonsMD: null,
  toolbarButtonsSM: null,
  toolbarButtonsXS: null,
  scaytOptions: {
    enableOnTouchDevices: false,
    localization: 'en',
    extraModules: 'ui',
    spellcheckLang: 'en_US',
    contextMenuSections: 'suggest|moresuggest',
    serviceProtocol: 'http(s)',
    servicePort: 'your_port_number',
    serviceHost: 'your_host_name',
    servicePath: 'spellcheck/script/ssrv.fcgi',
    contextMenuForMisspelledOnly: true,
    scriptPath: 'http(s)://your_host_name/spellcheck/wscbundle/wscbundle.js'
  }
});
```

## 4. Configuring SCAYT

Define additional SCAYT parameters and change the default values, for example, change default spell checking language. You can find a full list of SCAYT API (WProofreader) parameters and possible values on the [API page](#) and [WProofreader Customization Options](#) section.