

# SCAYT parameters for CKEditor

Here you can find a list of all available SCAYT parameters for CKEditor 4.0+ that can be used for the SCAYT configuration. Also, you may visit [CKEDITOR configuration documentation](#).

- [grayt\\_autoStartup](#)
- [scayt\\_inlineModelImmediateMarkup](#)
- [scayt\\_maxSuggestions](#)
- [scayt\\_minWordLength](#)
- [scayt\\_customerId](#)
- [scayt\\_ignoreAllCapsWords](#)
- [scayt\\_ignoreDomainNames](#)
- [scayt\\_ignoreWordsWithMixedCases](#)
- [scayt\\_ignoreWordsWithNumbers](#)
- [scayt\\_disableOptionsStorage](#)
- [scayt\\_moreSuggestions](#)
- [scayt\\_contextCommands](#)
- [scayt\\_sLang](#)
- [scayt\\_uiTabs](#)
- [scayt\\_serviceProtocol](#)
- [scayt\\_serviceHost](#)
- [scayt\\_servicePort](#)
- [scayt\\_servicePath](#)
- [scayt\\_srcUrl](#)
- [scayt\\_customDictionaryIds](#)
- [scayt\\_userDictionaryName](#)
- [scayt\\_contextMenuItemsOrder](#)
- [scayt\\_elementsToIgnore](#)
- [scayt\\_multiLanguageMode](#) DEPRECATED | WSC 5.3.2
- [scayt\\_multiLanguageStyles](#) DEPRECATED | WSC 5.3.2

## scayt\_autoStartup

|                  |                                                                                               |
|------------------|-----------------------------------------------------------------------------------------------|
| Description:     | <b>scayt_autoStartup</b> parameter turns SCAYT on/off automatically after the editor loading. |
| Parameter type:  | Boolean                                                                                       |
| Possible values: | <ul style="list-style-type: none"><li>• true</li><li>• false</li></ul>                        |

Example:

```
config.scayt_autoStartup = true;
```

[Back to the top...](#)

## grayt\_autoStartup

|                  |                                                                                                                   |
|------------------|-------------------------------------------------------------------------------------------------------------------|
| Description:     | <b>grayt_autoStartup</b> parameter turns Grammar As You Type (GRAYT) on/off automatically once SCAYT has started. |
| Parameter type:  | Boolean                                                                                                           |
| Default value:   | true                                                                                                              |
| Possible values: | <ul style="list-style-type: none"><li>• true</li><li>• false</li></ul>                                            |

Example:

```
config.grayt_autoStartup = false;
```

[Back to the top...](#)

## scayt\_inlineModelImmediateMarkup

|                  |                                                                                                                                                                                                                                                    |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description:     | <b>scayt_inlineModeImmediateMarkup</b> parameter turns the SCAYT initiation on/off when Inline CKEditor is not focused. The SCAYT markup is taken place (SCAYT instance is not destroyed) in both Inline CKEditor's states, focused and unfocused. |
| Parameter type:  | Boolean                                                                                                                                                                                                                                            |
| Default value:   | false                                                                                                                                                                                                                                              |
| Possible values: | <ul style="list-style-type: none"> <li>• true</li> <li>• false</li> </ul>                                                                                                                                                                          |

Example:

```
config.scayt_inlineModeImmediateMarkup = true;
```

[Back to the top...](#)

## scayt\_maxSuggestions

|                  |                                                                                                                                                                                                                                                                                                                                                                 |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description:     | <b>scayt_maxSuggestions</b> parameter defines the number of SCAYT suggestions to show in the main context menu.                                                                                                                                                                                                                                                 |
| Parameter type:  | Number                                                                                                                                                                                                                                                                                                                                                          |
| Default value:   | 3                                                                                                                                                                                                                                                                                                                                                               |
| Possible values: | <ul style="list-style-type: none"> <li>• 0 (zero) – No suggestions are shown in the main context menu. All suggestions will be shown in the "More Suggestions" sub-menu.</li> <li>• positive number – The max number of suggestions to show in the main context menu. Other entries will be listed in "More Suggestions".</li> <li>• negative number</li> </ul> |

Example:

```
config.scayt_maxSuggestions = 3;
```

[Back to the top...](#)

## scayt\_minWordLength

|                  |                                                                                                                                            |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Description:     | <b>scayt_minWordLength</b> parameter defines the minimum length of the words that will be collected from editor's text for spell checking. |
| Parameter type:  | Number                                                                                                                                     |
| Default value:   | 3                                                                                                                                          |
| Possible values: | any positive number                                                                                                                        |

Example:

```
config.scayt_minWordLength = 2;
```

[Back to the top...](#)

## scayt\_customerId

|                  |                                                                                                                                                                                                                                                                                                                                                      |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description:     | <b>scayt_customerId</b> parameter sets a customer ID for Cloud SCAYT. It is required for migration from free, ad-supported version to paid, ad-free version. <div>  <b>scayt_customerId</b> is intended for use only with the <b>Cloud version of SCAYT</b>. </div> |
| Parameter type:  | String                                                                                                                                                                                                                                                                                                                                               |
| Default value:   | The free version of SCAYT plugin is shipped with already predefined service ID value.                                                                                                                                                                                                                                                                |
| Possible values: | your-service-id                                                                                                                                                                                                                                                                                                                                      |

Example:

```
config.scayt_customerId = 'your-service-id';
```

[Back to the top...](#)

## scayt\_ignoreAllCapsWords

|                  |                                                                                                      |
|------------------|------------------------------------------------------------------------------------------------------|
| Description:     | <b>scayt_ignoreAllCapsWords</b> parameter regulates whether all capitalized words should be ignored. |
| Parameter type:  | Boolean                                                                                              |
| Default value:   | false                                                                                                |
| Possible values: | <ul style="list-style-type: none"> <li>true</li> <li>false</li> </ul>                                |

Example:

```
config.scayt_ignoreAllCapsWords = true;
```

[Back to the top...](#)

## scayt\_ignoreDomainNames

|                  |                                                                                                              |
|------------------|--------------------------------------------------------------------------------------------------------------|
| Description:     | <b>scayt_ignoreDomainNames</b> parameter regulates whether domain names and web addresses should be ignored. |
| Parameter type:  | Boolean                                                                                                      |
| Default value:   | false                                                                                                        |
| Possible values: | <ul style="list-style-type: none"> <li>true</li> <li>false</li> </ul>                                        |

Example:

```
config.scayt_ignoreDomainNames = true;
```

[Back to the top...](#)

## scayt\_ignoreWordsWithMixedCases

|                 |                                                                                                                     |
|-----------------|---------------------------------------------------------------------------------------------------------------------|
| Description:    | <b>scayt_ignoreWordsWithMixedCases</b> parameter regulates whether words with mixed case letters should be ignored. |
| Parameter type: | Boolean                                                                                                             |

|                  |                                                                           |
|------------------|---------------------------------------------------------------------------|
| Default value:   | false                                                                     |
| Possible values: | <ul style="list-style-type: none"> <li>• true</li> <li>• false</li> </ul> |

Example:

```
config.scayt_ignoreWordsWithMixedCases = true;
```

[Back to the top...](#)

## scayt\_ignoreWordsWithNumbers

|                  |                                                                                                             |
|------------------|-------------------------------------------------------------------------------------------------------------|
| Description:     | <b>scayt_ignoreWordsWithNumbers</b> parameter regulates whether words containing numbers should be ignored. |
| Parameter type:  | Boolean                                                                                                     |
| Default value:   | false                                                                                                       |
| Possible values: | <ul style="list-style-type: none"> <li>• true</li> <li>• false</li> </ul>                                   |

Example:

```
config.scayt_ignoreWordsWithNumbers = true;
```

[Back to the top...](#)

## scayt\_disableOptionsStorage

|                  |                                                                                                                                                                                                                                  |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description:     | <b>scayt_disableOptionsStorage</b> parameter defines whether SCAYT options storing should be disabled. It is allowed to pass an array of options.                                                                                |
| Parameter type:  | Array                                                                                                                                                                                                                            |
| Default value:   | ''                                                                                                                                                                                                                               |
| Possible values: | <ul style="list-style-type: none"> <li>• ''</li> <li>• scayt_ignoreAllCapsWords</li> <li>• scayt_ignoreDomainNames</li> <li>• scayt_ignoreWordsWithMixedCases</li> <li>• scayt_ignoreWordsWithNumbers</li> <li>• lang</li> </ul> |

Example:

```
config.scayt_disableOptionsStorage = ['lang', 'ignore-all-caps-words', 'ignore-words-with-mixed-cases'];
```

[Back to the top...](#)

## scayt\_moreSuggestions

|                 |                                                                                                              |
|-----------------|--------------------------------------------------------------------------------------------------------------|
| Description:    | <b>scayt_moreSuggestions</b> parameter enables/disables the "More Suggestions" sub-menu in the context menu. |
| Parameter type: | String                                                                                                       |
| Default value:  | on                                                                                                           |

|                  |         |
|------------------|---------|
| Possible values: | on, off |
|------------------|---------|

Example:

```
config.scayt_moreSuggestions = 'off';
```

[Back to the top...](#)

## scayt\_contextCommands

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description:     | <p><b>scayt_contextCommands</b> parameter manages and customizes the SCAYT context menu commands: Add Word, Ignore All, Options, Languages, Dictionaries and About. It is allowed to pass more than one value separating each value with a vertical bar.</p> <div>  Options, Languages and Dictionaries items can be added to the SCAYT context menu only if these items are present on the SCAYT settings dialog. The visibility of these items are regulated by the <a href="#">scayt_uiTabs</a> parameter. </div>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Parameter type:  | Array                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Default value:   | ignore ignoreall add                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Possible values: | <ul style="list-style-type: none"> <li>ignoreall add option language dictionary about – Show in the SCAYT context menu <b>Ignore All</b>, <b>Add Word</b>, <b>Options</b>, <b>Languages</b>, <b>Dictionaries</b>, and <b>About</b> options.</li> <li>off – Do not show any additional commands in the context menu except a list of main suggestions and the <b>More Suggestions</b> sub-menu.</li> <li>all – Enable all available commands in the context menu.</li> <li>ignoreall – Add the <b>Ignore All</b> command to the context menu.</li> <li>add – Add only the <b>Add Word</b> command to the context menu.</li> <li>option – Add the <b>Options</b> item to the context menu.</li> <li>language – Add the <b>Languages</b> item to the context menu. It opens the <b>Languages</b> tab of the SCAYT settings dialog. The <b>Languages</b> tab contains the list of the available languages for spell checking and is used for setting the default spell checking language.</li> <li>dictionary – Add the <b>Dictionaries</b> item to the context menu. It opens the <b>Dictionary</b> tab of the SCAYT settings dialog. The <b>Dictionaries</b> tab is used for the personal user dictionary management. It allows users to create personal dictionaries with custom words such as complex words, acronyms, proper names, and others and use them while working with the system.</li> <li>about – Enable the <b>About</b> menu item.</li> </ul> |

Example:

```
//Show only the Add Word and Ignore All commands in the context menu.
config.scayt_contextCommands = 'add|ignoreall';
```

[Back to the top...](#)

## scayt\_sLang

|                  |                                                                                                                                             |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Description:     | <b>scayt_sLang</b> parameter sets a language short code of the default language that will be used for spell checking.                       |
| Parameter type:  | String                                                                                                                                      |
| Default value:   | en_US (American English)                                                                                                                    |
| Possible values: | <ul style="list-style-type: none"> <li><a href="#">Default languages list</a></li> <li><a href="#">Additional languages list</a></li> </ul> |

Example:

```
//Set the default language to German (de_DE).
config.scayt_sLang = 'de_DE';
```

[Back to the top...](#)

## scayt\_uiTabs

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description:     | <p><b>scayt_uiTabs</b> parameter customizes the SCAYT settings dialog and manages visibility of particular tabs there such as Options, Languages, and Dictionaries.</p> <div> By default, SCAYT settings dialog contains four tabs, namely <b>Options</b>, <b>Languages</b>, <b>Dictionaries</b>, and <b>About</b>. The <b>About</b> tab is used to provide the information about the SCAYT version and copyrights. Unlike <b>Options</b>, <b>Languages</b>, <b>Dictionaries</b> tabs, it can't be removed.</div> |
| Parameter type:  | Array                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Default value:   | 1,1,1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Possible values: | <ul style="list-style-type: none"><li>• 0,0,0 – Hide all customizable tabs: <b>Options</b>, <b>Languages</b>, and <b>Dictionaries</b>.</li><li>• 0,1,0 – Hide the <b>Options</b> and <b>Dictionaries</b> tabs.</li><li>• 0,0,1 – Hide the <b>Options</b> and <b>Languages</b> tabs.</li><li>• 1,1,0 – Hide the <b>Dictionaries</b> tab.</li><li>• 1,0,1 – Hide the <b>Language</b> tab.</li><li>• 1,1,1 – Show all tabs: <b>Options</b>, <b>Languages</b>, and <b>Dictionaries</b>.</li></ul>                                                                                                      |

Example:

```
//Hide the Languages tab.
config.scayt_uiTabs = '1,0,1';
```

[Back to the top...](#)

## scayt\_serviceProtocol

|                  |                                                                                                                                                                                                                                                                                                                                                                                             |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description:     | <p><b>scayt_serviceProtocol</b> parameter specifies a protocol to access the SCAYT service. If this parameter is not specified, the protocol will be automatically defined based on the script location.</p> <div> This is the parameter that intended for us with the <b>Server version</b> only.</div> |
| Parameter type:  | String                                                                                                                                                                                                                                                                                                                                                                                      |
| Default value:   | https                                                                                                                                                                                                                                                                                                                                                                                       |
| Possible values: | <ul style="list-style-type: none"><li>• http</li><li>• https</li></ul>                                                                                                                                                                                                                                                                                                                      |

Example:

```
config.scayt_serviceProtocol='https';
```

[Back to the top...](#)

---

## scayt\_serviceHost

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description:     | <p><b>scayt_serviceHost</b> parameter specifies a service host name to access the SCAYT service. If this parameter is not specified clearly, the service host will be automatically defined based on the script location.</p> <div> The SCAYT plugin which is shipped with the default CKEditor packages is pointed to the WebSpellChecker Cloud services. <b>scayt_serviceHost</b> is already predefined in the plugin configuration.</div> <p>If you are using the <b>Server version</b>, you need to specify the <b>host name</b> that you used during the installation of WebSpellChecker.</p> |
| Parameter type:  | String                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Default value:   | <a href="https://svc.webspellchecker.net">svc.webspellchecker.net</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Possible values: | <ul style="list-style-type: none"><li>• <a href="https://svc.webspellchecker.net">svc.webspellchecker.net</a> – The default WebSpellChecker service host name. It is used for the WebSpellChecker Cloud services subscriptions.</li><li>• <code>your_host_name</code></li></ul>                                                                                                                                                                                                                                                                                                                                                                                                     |

Example:

```
config.scayt_serviceHost='your_host_name';
```

[Back to the top...](#)

---

## scayt\_servicePort

|                  |                                                                                                                                                                                                                                                                                                  |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description:     | <p><b>scayt_servicePort</b> parameter specifies a service port that will be used to access the SCAYT service.</p> <div> This is the parameter that intended for us with the <b>Server version</b> only.</div> |
| Parameter type:  | String                                                                                                                                                                                                                                                                                           |
| Default value:   | 80                                                                                                                                                                                                                                                                                               |
| Possible values: | <p>Any available port.</p> <ul style="list-style-type: none"><li>• 2880 – default port that listens WebSpellChecker AppServer. Use this port if your are using the Server version.</li></ul>                                                                                                     |

Example:

```
config.scayt_servicePort = '2880';
```

[Back to the top...](#)

---

## scayt\_servicePath

|                 |                                                                                                           |
|-----------------|-----------------------------------------------------------------------------------------------------------|
| Description:    | <p><b>scayt_servicePath</b> parameter specifies a path that will be used to access the SCAYT service.</p> |
| Parameter type: | String                                                                                                    |
| Default value:  | <code>/virtual_directory/script/ssrv.fcgi</code>                                                          |

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Possible values: | <ul style="list-style-type: none"> <li>Path to the <b>ssrv.fcgi</b> script. Use this if you are using the older versions of WebSpellChecker v4.x and the connection between your app and AppServer is configured via FastCGI protocol (using SSRV.cgi component).</li> <li>Use <b>'/'</b> if you are using the newer versions of WebSpellChecker v5.x. and you configured the direct connection with AppServer. In this case also use <b>config.scayt_servicePort = "2880";</b>.</li> </ul> |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Example:

```
config.scayt_servicePath = 'virtual_directory/script/ssrv.fcgi';
```

Or

```
config.scayt_servicePath = '/';
```

[Back to the top...](#)

## scayt\_srcUrl

|                  |                                                                                                                                                                                                                                                   |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description:     | <b>scayt_srcUrl</b> parameter specifies a URL to the SCAYT core.<br><div>  <b>scayt_srcUrl</b> is intended for use only with the Server version of SCAYT. </div> |
| Parameter type:  | String                                                                                                                                                                                                                                            |
| Default value:   | http(s)://your_host_name/virtual_directory/wscbundle/wscbundle.js                                                                                                                                                                                 |
| Possible values: | <ul style="list-style-type: none"> <li>http(s)://your_host_name/virtual_directory/wscbundle/wscbundle.js</li> <li>http(s)://your_host_name/virtual_directory/lf/scayt3/ckscayt/ckscayt.js</li> </ul>                                              |

Example:

```
config.scayt_srcUrl = 'http(s)://your_host_name/virtual_directory/wscbundle/wscbundle.js';
```

[Back to the top...](#)

## scayt\_customDictionaryIds

|                  |                                                                                                             |
|------------------|-------------------------------------------------------------------------------------------------------------|
| Description:     | <b>scayt_customDictionaryIds</b> parameter specifies a custom dictionary ID that will be linked with SCAYT. |
| Parameter type:  | String                                                                                                      |
| Default value:   | None                                                                                                        |
| Possible values: | IDs of custom dictionaries.                                                                                 |

Example:

```
config.scayt_customDictionaryIds = '3021,3456,3478';
```

[Back to the top...](#)

## scayt\_userDictionaryName

|                 |                                                                                                               |
|-----------------|---------------------------------------------------------------------------------------------------------------|
| Description:    | <b>scayt_userDictionaryName</b> parameter predefines a specific user dictionary that will be used with SCAYT. |
| Parameter type: | String                                                                                                        |

|                  |                                |
|------------------|--------------------------------|
| Default value:   | None                           |
| Possible values: | Any name of a user dictionary. |

Example:

```
config.scayt_userDictionaryName='user_dictionary_name';
```

[Back to the top...](#)

## scayt\_contextMenuItemsOrder

|                  |                                                                                                                                                                                                                     |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description:     | <b>scayt_contextMenuItemsOrder</b> parameter defines the order of SCAYT context menu items by groups. This must be a string with one or more of the following words separated by a pipe character (' ').            |
| Parameter type:  | String                                                                                                                                                                                                              |
| Default value:   | suggest moresuggest control                                                                                                                                                                                         |
| Possible values: | <ul style="list-style-type: none"> <li>• suggest – main suggestion word list;</li> <li>• moresuggest – more suggestions word list;</li> <li>• control – SCAYT commands, such as "Ignore" and "Add Word".</li> </ul> |

Example:

```
config.scayt_contextMenuItemsOrder = 'moresuggest|control|suggest';
```

[Back to the top...](#)

## scayt\_elementsToIgnore

|                  |                                                                                                       |
|------------------|-------------------------------------------------------------------------------------------------------|
| Description:     | <b>scayt_elementsToIgnore</b> parameter defines HTML tags that will be ignored during check spelling. |
| Parameter type:  | String                                                                                                |
| Default value:   | 'style'                                                                                               |
| Possible values: | Any HTML tag                                                                                          |

Example:

```
config.scayt_elementsToIgnore='del,pre';
```

[Back to the top...](#)

## scayt\_multiLanguageMode DEPRECATED | WSC 5.3.2

|                 |                                                                                                                                                                                                                                                                                                                                                                                               |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description:    | <b>scayt_multiLanguageMode</b> parameter turns on/off a special multi-language support mode. <div>            scayt_multiLanguageMode parameter was specifically designed to work with a certain language plugin for CKEditor. Before using this parameter, CKEditor Language plugin must be added. </div> |
| Parameter type: | Boolean                                                                                                                                                                                                                                                                                                                                                                                       |
| Default value:  | false                                                                                                                                                                                                                                                                                                                                                                                         |

|                  |                                                                                                                                       |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Possible values: | <ul style="list-style-type: none"> <li>• true – multi-language support turns on after the editor loading.</li> <li>• false</li> </ul> |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------|

Example:

```
config.scyt_multiLanguageMode='true';
```

[Back to the top...](#)

## scyt\_multiLanguageStyles DEPRECATED | WSC 5.3.2

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description:     | <p><b>scyt_multiLanguageStyles</b> parameter allows defining additional styles for misspelled words specific for a particular language.</p> <div>  scyt_multiLanguageStyles can be used only if the <a href="#">_include_scyt_parameters_for_ckeditor4#scyt_multiLanguageMode</a> parameter is set to "true". </div>                                                                                                 |
| Parameter type:  | Object                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Default value:   | None                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Possible values: | <pre>{   'Language_short_code': 'background-image: none; color: #cc22cc',   'el': 'background-image: none; color: blue',   'nl': 'background-image: none; color: red',   'fi': 'background-image: none; color: indigo',   'fr': 'background-image: none; color: orange',   'de': 'background-image: none; color: green' };</pre> <div>  All short codes should be presented according ISO 639-1:2002 codes. </div> |

Example:

```
config.scyt_multiLanguageStyles= {'fr': 'color: green'};
```

[Back to the top...](#)