

License activation through proxy server

If you are trying to deploy the application and activate the license on a server which is running **behind the firewall** and the Internet connection (inbound and outbound traffic) is controlled by a **proxy server**, please follow the instructions below.

1. Before making any changes, it is recommended to stop AppServer.
2. Locate the **AppServerX.xml** configuration file in the WebSpellChecker installation folder on your server. The default path to the AppServerX.xml file is **<WebSpellChecker_Installation_Path>/AppServer/AppServerX.xml**
3. Scroll down to the section with parameters responsible for proxy server settings: **<Proxy>...</Proxy>**.
4. To enable the proxy server module, change the default value of **EnableProxy** from **false** to **true**. And fill in the rest of the values listed in the Proxy section.

AppServerX.xml

```
<Proxy>
    <EnableProxy>true</EnableProxy>
    <ProxyHost></ProxyHost>
    <ProxyPort></ProxyPort>
    <ProxyUserName></ProxyUserName>
    <ProxyPassword></ProxyPassword>
</Proxy>
```

The detailed description of each of these parameters is available under [AppServer parameters#Proxy](#) section.

5. As soon as the modifications are completed, [start AppServer](#) for the changes to take effect.
6. Proceed with manual license activation using [License activation on Linux](#) or [License activation on Windows](#) guides.