

Disable license auto-reactivation

There is a mechanism of license reactivation available and, by default, it is enabled. There will be a set of attempts to reactivate a license automatically that is about to expire (7 days, 1 day, 1 hour and 10 minutes before expiration). All the attempts and their status will be recorded in the log files.

If you do not wish the license to be auto-reactivated upon its expiration, you can disable [AppServer parameters#AutoLicenseReactivation](#) option.

1. Before making any changes, it is recommended to **stop AppServer** ([Main AppServer commands#stopAppServerWindowsLinux2.StopAppServer](#)).
2. Locate the **AppServerX.xml** configuration file in the WebSpellChecker installation folder on your server. The default path to the AppServerX.xml file is **<WebSpellChecker_Installation_Path>/AppServer/AppServerX.xml**
3. Scroll down to the section with parameters responsible for licensing: **<License>...</License>**.
4. For **AutoLicenseReactivation** parameter change the default value from **true** to **false**, to disable the license reactivation attempts.

AppServerX.xml

```
<AutoLicenseReactivation>false</AutoLicenseReactivation>
```

5. As soon as the modifications are completed, [start AppServer](#) for the changes to take effect.



Since the auto-reactivation will be disabled, you are responsible for ensuring timely activation of the license manually. Otherwise, the spell and grammar check functionality stops working.