

Detect language command

The **detect_language** command is available since the release of WebSpellChecker v5.5.8 in March 2020. It detects the language(s) of a given text.

- This functionality is built on top of the [Compact Language Detector 2 \(CLD2\)](#) library.
- It supports over 80 languages.
- In a single request it can detect and return up to 3 languages with a proportion ration of each language in the text.
- To reach the better and more accurate result, it is recommended to split your text into sentences and send as separate requests.
- If the language is not detected, it will be returned as Unknown.



Command name: detect_language

#	Parameter	Possible values	Default value	Description
1	text	• plain text		A piece of text which will be sent for language detection.
2	customerid	• your-service-id value		A special service ID value (activation key) that has to be passed to a request query. It's obtained upon subscription to the Cloud services (paid or trial).
3	format	• json • xml	json	The response format for output data.

Response structure

#	Name	Description
1	LangShortCode	A language short code. Supported languages
2	LangName	A full name of a detected language.
3	Proportion	The proportion ration of the detected language in the text.

Example 1.1

Request URL (GET):

`http(s)://svc.webspellchecker.net/api?cmd=detect_language&text=this sampl text demonstrates the work of the Web API service.&customerid=[your-service-id]`

Parameters:

- Command: *detect_language*
- Text: *this sampl text demonstrates the work of the Web API service.*

Request response:

```
{
  "LangShortCode": "en_US",
  "LangName": "American English",
  "Proportion": 0.98
}
```